

RR SERIES

RR4010

4 CHANGE-OVER CONTACTS, 14 PINS, FPDT.

TYPE

RR4010 ... V
Relay for Railway
4 CO

MAX. CONTACT LOAD

6 A / 250 V AC1
6 A / 30 V DC1

CONTACT

Material	Standard	AgNi
	Optional	AgNi + 0,2 μ Au
	Optional	AgNi + 10 μ Au
Rated current / Max. peak current		6 A / 15 A
Rated voltage / Max. switching voltage AC-1		250 V / 250 V
Rated load AC15 (250 V)		350 VA
Min. switching load		10 mA / 10 V 5 mA / 5 V (10 μ Au)

COIL

Operation range	$0,7 \times U_N \dots 1,25 \times U_N$
Rated power (AC/DC)	1,4 W
Release voltage	$\geq 0,1 \times U_N$
Coil resistance	$\pm 10\%$

Coil data

VDC	Ω	mA
24	426	56
48	1K5	32
72	3K4	21
110	8K2	13

INSULATION (Vrms, 1 min)

Contact open	1,5 kV / 850 V
Coil / Contacts	4 kV / 2200 V
Insulation IEC 61810-1	2,5 kV/3
Between contacts	4 kV / 2200 V



SPECIFICATIONS

Ambient temperature	- 40 °C ... + 80 °C
Operation / Release time	20 ms / 15 ms
Protection category	IP40
Electrical life DC / Mechanical life	1·10 ⁵ op / 10·10 ⁶ op (AC) 20·10 ⁶ op (DC)
Weight	90 g

ACCESSORIES

Sockets	SMT40D, SMW40F, SMP40X, SMP40F
---------	--------------------------------

ORDERING CODE



CONNECTION DIAGRAM




FIG. 1 ELECTRICAL LIFE AC LOAD






FIG. 2 MAX. DC BREAKING CAPACITY



DIMENSIONS mm [inch]



TECHNICAL APPROVALS



IEC 61810; EN 60947